



Phoenix T20 Series Tillers

Four Super Heavy Duty Gear Drive Models from 68 to 90 Inches



T20 Series Rotary Tillers from Phoenix Line assure you years of trouble free performance even under the most demanding applications. The load bearing frame on which the protective hood and transmission are mounted make this machine extremely sturdy. The unique design dramatically reduces the possibility of clogging, even in sticky or wet soil conditions.

Standard Features Include:

- Heavy Duty Series 6 PTO with Heavy Duty Friction Disc Slip Clutch by Eurocardan
- Lateral Gear Drive in Oil Bath.
- 6 Tines Per Flange
- Heavy Duty Adjustable Upper and Lower Hitch Blocks
- Four Drag Board Chains on Two Section Drag Board for Ease of Adjustment
- Oversized Sealed Bearings

Specifications	T20-68GE	T20-72GE	T20-80GE	T20-90GE
Working Width (In.)	68	72	80	90
Working Depth (In.)	7	7	7	7
Blades / Flange	6	6	6	6
Total Blades	42	42	48	54
Side Drive	Gear	Gear	Gear	Gear
Driveline Protection	Slip Clutch	Slip Clutch	Slip Clutch	Slip Clutch
Hitch	Cat I and II	Cat I and II	Cat I and II	Cat I and II
PTO Shaft Series	6	6	6	6
PTO Power Required (HP)	40-70	40-70	40-70	40-70
Optimum PTO Speed(RPM)	540	540	540	540
Rotor Flange Diameter (In.)	6.3	6.3	6.3	6.3
Rotor Flange Thickness (In.)	0.5	0.5	0.5	0.5
Approximate Weight W/PTO (LBS)	933	977	1021	1065